




INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification ⁶ : A61M 25/00, A61B 5/042	A1	(11) International Publication Number: WO 99/30762 (43) International Publication Date: 24 June 1999 (24.06.99)
(21) International Application Number: PCT/US98/26645 (22) International Filing Date: 15 December 1998 (15.12.98) (30) Priority Data: 08/993,217 18 December 1997 (18.12.97) US (71) Applicant: MEDTRONIC, INC. [US/US]; 7000 Central Avenue, N.E., Minneapolis, MN 55432 (US). (72) Inventors: LI, Hong; 10230 N. Foothill Boulevard #E17, Cupertino, CA 95014 (US). GAISER, John, W.; 910 Bush Street, Mountain View, CA 94041 (US). (74) Agents: HANN, James, F. et al.; Townsend and Townsend and Crew LLP, 8th floor, Two Embarcadero Center, San Francisco, CA 94111-3834 (US).		(81) Designated States: AU, CA, JP, European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE). Published <i>With international search report.</i> <i>Before the expiration of the time limit for amending the claims and to be republished in the event of the receipt of amendments.</i>
(54) Title: PRECURVED, DUAL CURVE CARDIAC INTRODUCER SHEATH (57) Abstract <p>A precurved cardiac introducer sheath (4) includes an elongate, hollow body having main and tip portions (24, 22). The tip portion includes first through fifth segments (26, 28, 30, 32, 34). The first, second, and third segments lie in a first plane (36) while the fourth and fifth segments lie in a second plane (38) oriented at a second angle (37) of about ± 10 to 170° to the first plane. The second segment defines an arc extending along a first, included angle of about 90–110° while the fourth segment defines an arc extending along a third, included angle of about 90–140°. The first, third, and fifth segments are preferably generally straight segments. The precurved introducer sheath is preferably configured to direct the electrophysiology catheter (18) directly at the posterior region (52) of the left atrium (40). The precurved introducer sheath is preferably housed within an outer introducer sheath (46) having a radially deflectable distal end (46), or a fixed distal curve.</p>		



FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AL	Albania	ES	Spain	LS	Lesotho	SI	Slovenia
AM	Armenia	FI	Finland	LT	Lithuania	SK	Slovakia
AT	Austria	FR	France	LU	Luxembourg	SN	Senegal
AU	Australia	GA	Gabon	LV	Latvia	SZ	Swaziland
AZ	Azerbaijan	GB	United Kingdom	MC	Monaco	TD	Chad
BA	Bosnia and Herzegovina	GE	Georgia	MD	Republic of Moldova	TG	Togo
BB	Barbados	GH	Ghana	MG	Madagascar	TJ	Tajikistan
BE	Belgium	GN	Guinea	MK	The former Yugoslav Republic of Macedonia	TM	Turkmenistan
BF	Burkina Faso	GR	Greece			TR	Turkey
BG	Bulgaria	HU	Hungary	ML	Mali	TT	Trinidad and Tobago
BJ	Benin	IE	Ireland	MN	Mongolia	UA	Ukraine
BR	Brazil	IL	Israel	MR	Mauritania	UG	Uganda
BY	Belarus	IS	Iceland	MW	Malawi	US	United States of America
CA	Canada	IT	Italy	MX	Mexico	UZ	Uzbekistan
CF	Central African Republic	JP	Japan	NE	Niger	VN	Viet Nam
CG	Congo	KE	Kenya	NL	Netherlands	YU	Yugoslavia
CH	Switzerland	KG	Kyrgyzstan	NO	Norway	ZW	Zimbabwe
CI	Côte d'Ivoire	KP	Democratic People's Republic of Korea	NZ	New Zealand		
CM	Cameroon			PL	Poland		
CN	China	KR	Republic of Korea	PT	Portugal		
CU	Cuba	KZ	Kazakistan	RO	Romania		
CZ	Czech Republic	LC	Saint Lucia	RU	Russian Federation		
DE	Germany	LI	Liechtenstein	SD	Sudan		
DK	Denmark	LK	Sri Lanka	SE	Sweden		
EE	Estonia	LR	Liberia	SG	Singapore		

PRECURVED, DUAL CURVE CARDIAC INTRODUCER SHEATH

5

BACKGROUND OF THE INVENTION

This invention relates to introducer sheaths used to introduce an electrophysiology catheter into the left atrium of the heart through a transseptal puncture and then direct the catheter to the target region within the left atrium. The invention is especially useful for directing the electrophysiology catheter to the posterior region of the left atrium.

The heart includes a number of pathways which are responsible for the propagation of signals necessary for normal electrical and mechanical function. The present invention is concerned with treatment of tachycardia, abnormally rapid rhythms of the heart caused by the presence of an arrhythmogenic site or accessory pathway which bypasses or short circuits the normal pathways in the heart. Tachycardias may be defined as ventricular tachycardias (VTs) and supraventricular tachycardias (SVTs). VTs originate in the left or right ventricle and are typically caused by arrhythmogenic sites associated with or without underlying heart disease. SVTs originate in the atria and are typically caused by an accessory pathway.

Treatment of both ventricular and supraventricular tachycardias may be accomplished by a variety of approaches, including drugs, surgery, implantable pacemakers/defibrillators, and catheter ablation. While drugs may be the treatment of choice for many patients, drugs typically only mask the symptoms and do not cure the underlying cause. Implantable devices, on the other hand, usually can correct an arrhythmia only after it occurs. Surgical and catheter-based treatments, in contrast, will actually cure the problem usually by ablating the abnormal arrhythmogenic tissue or accessory pathway responsible for the tachycardia. The catheter-based treatments rely on the application of various

destructive energy sources to the target tissue including direct current electrical energy, radiofrequency electrical energy, laser energy, and the like.

Of particular interest to the present invention, are
5 radiofrequency (RF) ablation protocols which have proven to be highly effective in tachycardia treatment while exposing the patient to minimum side effects and risks. Radiofrequency catheter ablation is generally performed after an initial mapping procedure where the locations of the arrhythmogenic
10 sites and accessory pathways are determined. After mapping, a catheter having a suitable electrode is introduced to the appropriate heart chamber and manipulated so that the electrode lies proximate the target tissue. Radiofrequency energy is then applied through the electrode to the cardiac
15 tissue to ablate a region of the tissue which forms part of the arrhythmogenic site or the accessory pathway. By successfully destroying that tissue, the abnormal signaling patterns responsible for the tachycardia cannot be sustained. Methods and systems for performing RF ablation by controlling
20 temperature at the ablation site are described in U.S. Patent No. 5,540,681 entitled "Method and System for Radiofrequency Ablation of Tissue."

Catheters designed for mapping and ablation frequently include a number of individual electrode bands
25 mounted to the distal tip of the catheter so as to facilitate mapping of a wider area in less time, or to improve access to target sites for ablation. Such catheters are described in U.S. Patent No. 5,445,148 entitled "Intracardiac Electrical Potential Reference Catheter." Mapping and ablation catheters
30 may facilitate rotational positioning of the distal tip, either by rotating the entire catheter from the proximal end, or by exerting torque on a core wire secured to the distal tip without rotating the catheter body itself. See U.S. Patent No. 5,545,200 entitled "Steerable Electrophysiology Catheter."
35 Introducer catheters or sheaths having precurved distal ends have been used for guiding cardiac catheters as well as other types of catheters. See, for example, U.S. Patent No.

5,147,315 and European Patent Application Publication No. 0670168.

SUMMARY OF THE INVENTION

5 The present invention is directed to a cardiac introducer sheath especially adapted for accessing the posterior region of the left atrium of the heart.

 The cardiac introducer sheath includes an elongate, hollow body having a main portion and a precurved tip portion.
10 The tip portion includes first through fourth, and preferably first through fifth, segments. The first, second, and third segments lie in a first plane while the fourth and fifth segments lie in a second plane oriented at a second, plane angle to the first plane. The second segment defines an arc
15 extending along a first, arc angle while the fourth segment defines an arc extending along a third, arc angle. The first and third segments are preferably generally straight segments.

 The precurved introducer sheath is preferably constructed so that the electrophysiology catheter is directed
20 at various portions of the left atrium, and in particular to the posterior region of the left atrium. This is preferably achieved by making a first and third segments generally straight and the second segment with a first, arc angle of about 70-90° and a fourth segment with a third, arc angle of
25 about 40-90°. Having such relatively sharp curves for the second and fourth segments also permit the introducer sheath to be made of softer materials because the tip portion is more resistant to straightening at body temperatures caused by the passage of the electrophysiology catheter through the
30 introducer sheath. The relatively sharp curves for the second and fourth segments and the use of a relatively short fifth segment leaves room for a relatively long electrode-carrying tip of a linear ablation catheter to maneuver.

 Other features and advantages of the invention will
35 appear from the following description in which the preferred embodiments have been set forth in detail in conjunction with the accompanying drawings.

BRIEF DESCRIPTION OF THE DRAWINGS

Fig. 1 illustrates a catheter assembly including a precurved cardiac introducer sheath made according to the invention;

5 Fig. 2 is a simplified view of the introducer sheath of Fig. 1 in a first configuration;

Fig. 3 is similar to Fig. 2 but illustrates the distal portion of the introducer sheath in a second configuration;

10 Fig. 3A illustrates the range of angles for the second angle of Figs. 2 and 3 when looking toward the left atrium; and

Fig. 4 schematically illustrates the distal portions of the outer and inner cardiac introducer sheaths of Fig. 1 passing through the atrioventricular septum with the distal end of the outer sheath radially deflected and oriented to help direct the tip of the electrophysiology catheter at the posterior region of the left atrium.

20 DESCRIPTION OF THE PREFERRED EMBODIMENT

Fig. 1 illustrates a catheter assembly 2 including a precurved, inner cardiac introducer sheath 4 made according to the invention. Cardiac introducer sheath 4 is housed within an outer cardiac introducer sheath 6 extending from a proximal end adaptor or handle 8. Handle 8 is used if the outer sheath 6 has an active deflectable tip 14. Handle 8 include a manipulator 10, used to radially deflect tip 14, and a fluid port 16 to permit flushing of the lumen of sheath 6 with saline as is generally conventional. A deflectable electrophysiology catheter 18 passes through inner cardiac introducer sheath 4 and out through a distal open end 20 of the tip portion 22 of introducer sheath 4. Inner sheath 4, with catheter 18 therein, is introduced into outer sheath 6 through the open proximal end 23 of handle 8. Sheath 4 also typically includes a fluid port to permit flushing of its lumen.

Turning now also to Fig. 2, tip portion 22 is seen to extend from the main portion 24 of introducer sheath 4.

Tip portion 22 includes first, second, third, fourth, and fifth segments 26, 28, 30, 32, and 34. First, third, and fifth segments 26, 30, and 34 are all preferably straight while second and fourth segments 28 and 32 are arcuate segments. Segments 26, 30, and 34 preferably have lengths of about 70 cm to 90 cm, 4 cm to 6 cm, and 0.5 cm to 2.0 cm, respectively. More preferably, segments 26, 30, and 34 have lengths of about 75 cm to 80 cm, 4.5 cm to 5.5 cm, and 0.7 cm to 1.3 cm, respectively. First, second, and third segments 26, 28, and 30 lie in a first plane 36 while fourth and fifth segments 32, 34 lie in a second plane 38. Second segment 28 defines a first, arc angle of about 70-90°, which corresponds to a first, included angle 29 of about 90-110°. First and second planes 36, 38 are oriented at a second, plane angle 37 of about $\pm 10^\circ$ to $\pm 170^\circ$ to one another. Fourth segment 32 defines a third, arc angle of about 40-90°, which corresponds to a third, included angle 33 of 90-140°.

Tip portion 22 is configured so to direct electrophysiology catheter 18 towards the various regions of the left atrium. This is illustrated schematically in Fig. 4. Left atrium 40 is shown with outer cardiac introducer sheath 6 passing through the septum 42 at the fossa ovalis 44. Inner sheath 4 can be used alone, that is without outer sheath 6, if desired. As can be seen by comparing Figs. 1 and 4, the distal end 14 of outer introducer sheath 6 is preferably radially deflectable which not only helps guide outer introducer sheath 6 through the patient's vasculature, with catheter 18 and inner cardiac introducer sheath 4 housed therein, but also helps to provide appropriate positioning for catheter 18. The choice of first, included angle 29 depends upon the size of the heart, and stiffness of the EP catheter to be passed through the sheath. Third, included angle 33 is chosen to have larger included angles (smaller arc angles) over the specified range when it is desired to direct catheter 18 towards pulmonary veins at the lateral side of the left atrium. Smaller included angles (larger arc angles) for the third, included angle 33 are chosen when electrophysiology

catheter 18 is to be directed towards the pulmonary veins at the septal side.

Second angle 37 is chosen to be about: (a) plus 10-80° for target regions at the upper left atrium, posterior region; (b) minus 10-80° for the upper left atrium, anterior region; (c) plus 100-170° for the lower left atrium posterior region; and (d) minus 100-170° for the lower left atrium, anterior region. Typical targets for curves (a), (c) include the pulmonary veins. Typical targets for curves (b), (d) include the mitral annulus region. In both Figs. 2 and 3, second angle 37 is shown to be a positive angle; negative second angles 37 would find fourth and fifth segments 32, 34 extending on the opposite side of first plane 36. Fig. 3A illustrates second angle 37 as it appears when facing the left atrium.

In use, outer cardiac introducer sheath 6 houses precurved inner cardiac introducer sheath 4 which houses electrophysiology catheter 18. A guidewire (not shown) may be used to help guide distal end of outer sheath 6 into left atrium 40 through a puncture in the septum 42 at fossa ovalis 44. Once within left atrium 40, tip portion 22 of inner cardiac introducer sheath 4 is extended from distal end 14. The rotary orientation of sheaths 4, 6 and the shapes and sizes of segments 26, 28, 30, 32, 34 cause distal outer open end 20 of tip portion 22 to be directed at the posterior region 52 of left atrium 40 as suggested in Fig. 4. Radial deflection of distal end 14 of outer sheath 6 to the curved shape of Fig. 4 also helps to direct catheter 18. Deflectable electrophysiology catheter 18 can then be extended through open end 20 to permit the desired electrophysiology procedure, typically mapping followed by ablation, to be carried out in a conventional manner. If catheter 18 is a deflectable catheter, one or more additional manipulators, not shown, could be used to cause the distal end of electrophysiology catheter 18 to be deflected radially into a curve, or both radially into a curve and laterally. Similarly, it may be desired to be able to provide lateral deflection (torsion) for tip portion 22 of precurved inner cardiac introducer sheath 4

and/or for distal end 14 of outer cardiac introducer sheath 6. U.S. Patent Nos. 5,545,200; 5,397,304; 5,487,757 disclose various structures for radial and lateral deflection of catheter elements.

5 Any and all patents, applications, and printed publications referred to above are incorporated by reference.

 Modification and variation can be made through the disclosed embodiments without departing from the subject of the invention as defined in the following claims. For
10 example, a radially deflectable tip could be replaced by a precurved tip; alternatively, tip 14 of outer sheath 6 could be straight and take the shape of inner sheath 4.

WHAT IS CLAIMED IS:

1 1. A cardiac introducer sheath comprising:
2 an elongate, hollow body comprising a main portion
3 and a tip portion;
4 the tip portion comprising, in order, first, second,
5 third and fourth segments, the first segment extending from
6 the main portion;
7 the first, second, and third segments lying in a
8 first plane;
9 the second segment defining an arc extending along a
10 first, arc angle;
11 the fourth segment lying in a second plane, the
12 second plane oriented at second angle to the first plane; and
13 the fourth segment defining an arc extending along a
14 third, arc angle.

1 2. The cardiac introducer sheath according to
2 claim 1 wherein the tip portion further comprises a fifth
3 segment extending from the fourth segment.

1 3. The cardiac introducer sheath according to
2 claim 2 wherein the fifth segment lies in the second plane.

1 4. The cardiac introducer sheath according to
2 claim 1 wherein the first and third segments are straight
3 segments.

1 5. The cardiac introducer sheath according to
2 claim 1 wherein the second and fourth segments defines areas
3 with constant radii.

1 6. The cardiac introducer sheath according to
2 claim 1 wherein the first segment has a length of about 70 cm
3 to 90 cm.

1 7. The cardiac introducer sheath according to
2 claim 1 wherein the third segment has a length of about 4 cm
3 to 6 cm.

1 8. The cardiac introducer sheath according to
2 claim 2 wherein the fifth segment has a length of about 0.5 cm
3 to 2 cm.

1 9. The cardiac introducer sheath according to
2 claim 1 wherein the first, arc angle of the second segment is
3 about 70° to 90°.

1 10. The cardiac introducer sheath according to
2 claim 1 wherein the third, arc angle of the fourth segment is
3 about 40° to 90°.

1 12. The cardiac introducer sheath according to
2 claim 1 wherein the second angle is about $\pm 10^\circ$ to $\pm 170^\circ$.

1 13. A cardiac introducer sheath assembly
2 comprising:
3 an inner cardiac introducer sheath comprising:
4 an elongate, hollow body comprising a main
5 portion and a tip portion;
6 the tip portion comprising, in order, first,
7 second, third and fourth segments, the first segment
8 extending from the main portion;
9 the first, second, and third segments lying in
10 a first plane;
11 the second segment defining an arc extending
12 along a first, arc angle;
13 the fourth segment lying in a second plane, the
14 second plane oriented at second angle to the first plane;
15 and
16 the fourth segment defining an arc extending
17 along a third, arc angle;
18 an outer cardiac introducer sheath comprising an
19 elongate, hollow outer body, containing said inner cardiac

20 introducer, including an outer tip portion and an outer main
21 portion.

1 14. The assembly according to claim 13 wherein the
2 outer tip portion is a radially deflectable outer tip portion.

1 15. The assembly according to claim 13 wherein said
2 outer tip portion is more flexible than said outer main
3 portion.

1 16. The assembly according to claim 13 wherein the
2 outer tip portion takes on a curved shape imparted by said
3 inner cardiac introducer sheath.




FIG. 1.




FIG. 4.




FIG. 2




FIG. 3A.




FIG. 3.

INTERNATIONAL SEARCH REPORT

International Application No

PCT/US 98/26645

A. CLASSIFICATION OF SUBJECT MATTER

IPC 6 A61M25/00 A61B5/042

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC 6 A61M A61B

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	EP 0 711 573 A (DAIG CORP) 15 May 1996 see column 1, line 7-15 see column 6, line 19-32 see column 16, line 44 - column 19, line 12 see figures 12,13	1-10, 12, 13
A	US 5 300 032 A (HIBBS LEE ET AL) 5 April 1994 see column 2, line 44-49 see column 3, line 1-6 see column 4, line 1-5	14-16

☐ Further documents are listed in the continuation of box C.

☒ Patent family members are listed in annex.

* Special categories of cited documents :

"A" document defining the general state of the art which is not considered to be of particular relevance

"E" earlier document but published on or after the International filing date

"L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)

"O" document referring to an oral disclosure, use, exhibition or other means

"P" document published prior to the international filing date but later than the priority date claimed

"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

"X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

"Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.

"&" document member of the same patent family

Date of the actual completion of the international search

31 March 1999

Date of mailing of the international search report

13/04/1999

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 2
NL - 2280 HV Rijswijk
Tel. (+31-70) 340-2040, Tx. 31 651 epo nl,
Fax: (+31-70) 340-3016

Authorized officer

Bichlmayer, K-P

INTERNATIONAL SEARCH REPORT

Information on patent family members

International Application No

PCT/US 98/26645

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
EP 0711573 A	15-05-1996	US 5690611 A	25-11-1997
		CA 2160510 A	12-05-1996
		JP 8224314 A	03-09-1996
<hr/>			
US 5300032 A	05-04-1994	US 4950257 A	21-08-1990
		AU 4056489 A	02-04-1990
		CA 1322920 A	12-10-1993
		WO 9002579 A	22-03-1990
<hr/>			